



SPECIFICATION

| | |
|---------------------------|---|
| Model | PTDK4XGL500 |
| Camera | |
| Image Sensor | 1/2.8" Progressive Scan CMOS Sensor |
| Horizontal Resolution | 5MP |
| Compression | H.264/H.265 |
| S/N Ratio | 60db |
| PTZ | |
| Horizontal Rotation Speed | 30°/sec |
| Horizontal Rotation Range | 0°~180° |
| Tilt Rotation Speed | 25°/sec |
| Tilt Rotation Range | -45°~40° |
| Preset Points | 255 |
| Guard Tours | 8 groups |
| Guard Points | Max 20 points |
| Lens | |
| Focus Length | 3.35-10.05mm F1.7-F3.0 |
| Focus Control | 4X Optical Zoom |
| Night Vision | |
| Infrared LED | Φ 35x6PCS |
| IR Range | 30m |
| Day-night mode | AUTO |
| Network | |
| Network protocol | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP |
| ONVIF | Support (PROFILE S,PROFILE G,PROFILE T) |
| Network interface | Built-in RJ45 network interface,support 10M/100M IP DATA |
| Main Stream1 | 5MP(2592*1944)@20fps |
| Main Stream2 | 4MP(2560*1440)@25fps |
| Main Stream3 | 1080P(1920*1080)@30fps |
| Main Stream4 | 720P(1280*720)@30fps |
| Main Stream5 | / |
| Main Stream6 | / |
| Sub Stream1 | D1(720*480)@20fps |
| Sub Stream2 | CIF(352*288)@20fps |
| Sub Stream3 | / |
| Sub Stream4 | / |
| Interface | |
| Audio | Optional |
| Alarm | / |
| SD Card Slot | / |
| POE | Optional |
| General | |
| Weatherproof | IP66 |
| Operating Temperature | Indoor: 0°~ +40° Outdoor: -40°~ +60° |
| Operating Humidity | ≤90% Non Condensing |
| Power | DC12V/3A |
| Lightning Protection | Transient voltage 6000V |
| Dimension | 39.6x19.6x16(cm) |
| Weight | 1.35Kgs |