



| SPECIFICATION | |
|----------------------|--|
| Model NO. | BMSCHTC500FPE-ECO |
| Video Output Mode | AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps; CVBS |
| Camera | |
| Image Sensor | 1/3" CMOS Sensor |
| Image Resolution | 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Minimun Illumination | Color: 0.03 lux@F2.0, AGC ON; B/W: 0 lux with IR |
| Scanning System | Progressive Scan |
| Lens | |
| Focus Length | 3.6mm |
| Focus Control | Fixed |
| Lens Type | Fixed |
| Night Vision | |
| IR Cut Filter | YES |
| Infrared LED | 42μ x 2PCS |
| Light Distance | 25m |
| IR Status | AGC auto control |
| Camera Features | |
| Starlight | N/A |

| Day/Night | YES |
|-----------------------|---|
| OSD Menu | has OSD Menu, but without OSD joysticker on the cable |
| WDR | DWDR |
| итс | YES |
| Noise Reduction | DNR |
| Coaxial Audio | / |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |
| General | |
| Housing | Metal, IP67 |
| Bracket | YES |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 500mA |
| Dimension | 169(W) x 67.5(H) x 70(D)mm |
| Weight | 500g |